# Diethylaminoethanol





#### NORTH Metal and Chemical Co.

# 1. Company Identification and Product Hazard Overview:

**Product Name** : Diethylaminoethanol

**Synonyms** : DEAE, Diethylethanolamine, DEEA

**Recommended Use** : Used as a neutralizing agent in boiler treatment, and as a chemical intermediate in the production of floor

polishes, pesticides, coatings, and pharmaceuticals.

Manufactured for : North Metal and Chemical Company

> P. O. Box 1985 609 E. King St. York, PA USA 17405 York, PA USA 17403 Tel: 717-845-8646 Fax: 717-846-7350

Email: north@northmetal.net Website: www.northmetal.net

In Case of Emergency: Call CHEMTREC (24H): 1-800-424-9300

### 2. Hazard Identification:

#### **GHS Classification:**

Flammable Liquids (Category 3)

Acute Toxicity, Oral (Category 4)

Acute Toxicity, Inhalation (Category 3)

Acute Toxicity, Dermal (Category 3)

Skin Corrosion (Category 1B)

Serious Eye Damage (Category 1)

Skin Sensitization (Category 1)

Acute Aquatic Toxicity (Category 3)

Chronic Aquatic Toxicity (Category 3)

### Signal Word: DANGER

Pictograms: Flammable, Corrosion, Acute Toxicity



#### **Hazard Statements:**

: Flammable liquid and vapor

H302 + H312 + H332: Harmful if swallowed, in contact with skin or inhaled H314 : Causes severe skin burns and serious eye damage.

H317 : May cause an allergic skin reaction H318

: Causes serious eye damage

H412 : Harmful to aquatic life with long lasting effects

#### 2. Hazard Identification:

#### **Precautionary Statements:**

**Prevention:** 

P210 : Keep away from heat/sparks/open flames/hot surfaces - No smoking

P233 : Keep container tightly closed

P240 : Ground/Bond container and receiving equipment

P241 : Use explosion-proof electrical/ventilating/lighting equipment

P242 : Use only non-sparking tools

P243 : Take precautionary measures against static discharge
P261 : Avoid breathing dust/fume/gas/mist/vapors/spray
P264 : Wash contact area thoroughly after handling
P270 : Do not eat, drink, or smoke when using this product
P271 : Use only outdoors or in a well-ventilated area

P272 : Contaminated clothing should not be allowed out of the workplace

P273 : Avoid release to the environment

**P280** : Wear protective gloves/protective clothing/eye protection/face protection.

P281 : Use personal protective equipment as required

P303 + P361 +P353 : IF ON SKIN or hair: Remove/Take off immediately all contaminated clothing. Rinse skin with

water/shower

P333 + P313 : IF skin irritation or rash occurs: Get medical advice/attention.

P305 + P351 + P338 : IF IN EYES: rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P310 : Immediately call a POISON CENTER or doctor/physician

P301 + P312 : IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

P301 + P330 + P331 : IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P304 + P340 : IF INHALED: Remove person to fresh air and keep in position comfortable for breathing

P308 + P313 : IF exposed or concerned: Get medical advice/attention P361 : Remove/Take off immediately all contaminated clothing

P363 : Wash contaminated clothing before reuse.

P370 + P378 : In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

P403 + P235 : Store in a well-ventilated place. Keep cool.

P273 + P405 : Avoid release to the environment. Store Locked Up.

**P501** : Dispose of contents/container in accordance with local/state/federal regulations.

# 3. Composition/Information on Ingredient:

Chemical Name : 2-Diethylaminoethanol

**Chemical Family** : Amines **Chemical Formula** : C<sub>6</sub>H<sub>15</sub>NO

Substance:	CAS Number:	EC	Compo. (% )
2-Diethylamnioethanol	100-37-8	202-845-2	>99%



4. First Aid Measures:

General Advice: : Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous

area.

Eyes : Flush skin with running water for at least fifteen minutes. Remove any contact lenses. Get medical aid/

attention immediately. Continue to rinse eyes during transport to the hospital.

**Skin**: Remove contaminated clothing. Wash skin with plenty of running water and soap. Take victim

immediately to the hospital. Consult a physician.

**Ingestion**: If the product is swallowed, first rinse mouth. Give small amount of water to drink. Call doctor/

physician/poison center immediately. Do not induce vomiting. Never give anything by mouth to an unconscious person. If a person vomits, place him/her in recovery position so the vomit does not enter

lungs.

**Inhalation**: If safe to do so, remove individual from further exposure. Keep warm and at rest. If breathing has

ceased, give artificial respiration. Do not give mouth to mouth resuscitation. Get medical attention/

consult a physician immediately.

**Note to Physician**: Treat symptomatically.

**PPE for first responders**: Gloves and safety goggles are highly recommended.

# 5. Fire Fighting Measures:

Flash Point (°C) : 50 °C (122 °F) - closed cup

Flammable Limits : Upper explosion limit: 11.7% (V); Lower explosion limit: 1.4% (V)

Auto ignition Temp. : Not available.

Flammable Class : Not available.

**General Hazard**: Evacuate personnel downwind in-order to avoid inhalation of irritating and/or harmful fumes and smoke.

**Extinguishing Media**: Use water spray, alcohol-resistant foam, dry chemical, or carbon dioxide.

Special hazards arising

from the substance : Carbon oxides, Nitrogen Oxides (NOx)

Fire Fighting Procedures: Hazardous decomposition and combustion products such as carbon/nitrogen oxides can be formed if

product is burning. Cool exposed containers with water spray to prevent over heating.

Fire Fighting Equipment: Respiratory and eye protection are required for fire fighting personnel. Full protective equipment

(bunker gear) and self-contained breathing apparatus (SCBA) should be used for all indoor fires and any significant outdoor fires. Evacuate area and fight fire from safe distance or a protected location. Move

fire-exposed containers, if allowable without sacrificing the safety of the firefighters. If possible,

firefighters should control run-off water to prevent environmental contamination.

### 6. Accidental Release Measures:

Protective Gear for

**Personnel**: Wear respiratory protection. Avoid breathing vapors, mist, or gas. Ensure adequate ventilation.

Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to

form explosive concentrations. Vapors can accumulate in low areas.

Environmental

Precaution : Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the

environment must be avoided.

Methods and materials for containment and

cleaning up : Contain spillage, and then collect with an electronically protected vacuum cleaner or by wet-brushing

and place in container for disposal according to local regulations.

**Release Notes**: If spill could potentially enter any waterway, including intermittent dry creeks, contact local authorities.



# 7. Handling and Storage:

Handling

: Avoid contact with skin and eyes. Avoid inhalation of vapor or mist. Keep away from sources of ignition. No smoking. Take measures to prevent the build up of electrostatic charge.

Storage

: Store in a cool, dry well-ventilated area. Keep containers closed and up right when not in use. Keep product isolated from incompatible materials/conditions

# 8. Exposure Controls and Personal Protection:

Components with workplace control parameters

Component	CAS-No.	Value	Control	Basis
	07.00.110.		parameters	
N,N-	100-37-8	TWA	2 ppm	USA. ACGIH Threshold Limit Values
Diethylethanolamine				(TLV)
	Remarks	Upper Respiratory Tract irritation		
		Central Nervous System convulsion		lsion
		Danger of cutaneous absorption		
		TWA	10 ppm	USA. NIOSH Recommended
			50 mg/m3	Exposure Limits
		Potential for dermal absorption		
		TWA	10 ppm	USA. Occupational Exposure Limits
			50 mg/m3	(OSHA) - Table Z-1 Limits for Air
				Contaminants
		Skin designation		
		The value in mg/m3 is approximate.		
		TWA	10 ppm	USA. OSHA - TABLE Z-1 Limits for
			50 mg/m3	Air Contaminants - 1910.1000
		Skin notation		

#### **Engineering Controls**

: Use appropriate engineering controls to avoid contact with skin, eyes, and clothing. Wash hands before breaks and immediately after handling the product.

### **Personal Protective** Equipment

: Eyes and face: Tightly fitting safety goggles. Face shield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH.

Skin: Avoid direct contact with skin. Wear rubber gloves, apron, boots or whole bodysuit when handling this product. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of any contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Body Protection: Complete suit protecting against chemicals; flame retardant anti-static protective clothing. The type of protective equipment must be selected according to the concentration and amount of dangerous substance at the specific work place.

**Respiratory:** Where risk assessment shows air-purifying respirators are appropriate, use full-face respirator with multi-purpose combination respirator cartridges as a back up to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH.

Work Hygienic Practices: Facilities storing or using this material should be equipped with emergency eyewash, and a safety shower. Good personal hygiene practices should always be followed.

### Control of Environmental

Exposure

:Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.



9. Chemical and Physical Properties:

Appearance : Liquid Upper Explosive Limit : 10.1% (V)

Odor : Amine-like Vapor Pressure : 1 hPa (1 mmHg) @ 20°C

 Odor threshold
 : Not available
 : 9 hPa (7 mmHg) @ 22°C

 : 9 hPa (7 mmHg) @ 22°C
 : 4.05 - (Air = 1.0)

Color : Colorless Relative Density : 0.884 g/cm<sup>3</sup> @ 25°C

pH (1% Solution) : 10.5 - 12.0 Solubility : completely soluble @ 20°C

Melting Point : Not available

Freezing Point : -68°C Partition coefficient (n-octanol/water) : log POW: 0.21

**Boiling Range** : 161°C (322°F) - lit.

Flash Point : 51.7°C (122°F) - closed cup Specific Gravity : 0.88
Viscosity @ 20 °C : 3.5 cP Auto Ignition Temp. : 320°C

**Decomposition Temp.** : Not available Molecular Weight : 117.19

**Evaporation Rate** : .2

**Lower Explosive Limit** : 0.7% (V)

# 10. Stability and Reactivity:

Stability : The product is stable under recommended storage conditions. Flammable liquid and vapors, avoid

contact with heat

Possibility of

**Hazardous Reactions**: None under normal processing.

Hazardous

**Decomposition Products:** Thermal decomposition can lead to release of irritating gases and vapors. Nitrogen Oxides (NOx).

Carbon Oxides

**Incompatible Materials**: Strong oxidizing agents, Strong acids, Copper, Zinc, and Iron. Do not store near acids.

**Conditions to Avoid** : Heat, flames, sparks

### 11. Toxicological Information:

#### **Acute Toxicity Data:**

LD50 Oral - Rat - 1,300 mg/kg LC50 Inhalation - Rat - 4.6 mg/L

Remarks: Brain and Coverings - recordings from specific areas of CNS. Sense organs and Special Sense (Nose, Eye, Ear, and Taste)

Eye - Conjunctive irritation. Behavioral - Convulsions or effect on seizure threshold.

LD50 Dermal - Guinea Pig - 885 mg/kg

# Skin corrosion/irritation:

Skin - Rabbit

Result: Open irritation test

#### Serious eye damage/eye irritation:

Eyes - Rabbit

Result: Severe eye irritation

### Respiratory or skin sensitization:

Corrosive by inhalation. Corrosive to skin. May be absorbed through skin in harmful amounts.

#### Germ cell mutagenicity:

No data available

#### **Carcinogenicity:**

Mouse - oral: Tumorigenic: Neoplastic by RTECS criteria. Lungs, Thorax, or Respiration: Bronchiogenic carcinoma. Liver: Tumors This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as a probable, possible, or confirmed human carcinogen by IARC

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a probable, possible, or confirmed human carcinogen by NTP.

**OSHA:** No component of this product present at levels greater than or equal to 0.1% is identified as a probable, possible, or confirmed human carcinogen by OSHA.

Reproductive toxicity: No data available



### 11. Toxicological Information:

### Specific target organ toxicity - single exposure:

No data available

### **Specific target organ toxicity - repeated exposure:**

No data available

#### **Aspiration Hazard:**

No data available

#### **Additional Information:**

RTECS: KK5075000

Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin.

Cough, Shortness of breath, Headache, Nausea

Stomach - Irregularities - Based on Human Evidence

# 12. Ecological Information:

All work practices must be aimed at eliminating environmental contamination.

Toxicity

**Toxicity to fish:** LC50 - Leuciscus idus (Golden orfe) - 100 - 220 mg/l - 96h

Toxicity to daphnia and other aquatic

**Invertebrates:** EC50 - Daphnia magna (Water flea) - 83.6 mg/l - 48h

**Toxicity to algae:** EC50 - Algae - > 30 mg/l - 72h

**Biodegradability:** Biotic/Aerobic - Exposure time 14d

Bioaccumulative

Potential: No data available

Mobility in soil: No data available

Results of PBT and

vPvB assessment: PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other Adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Harmful to aquatic life.

# 13. Disposal Considerations:

**Disposal Method**: Dispose of waste at an appropriate waste disposal facility according to current applicable laws and

regulations.

For Large Spills : Contain material and call local authorities for emergency assistance.

**Product Disposal**: Dispose of at a supervised incineration facility or an appropriate waste disposal facility according to

current applicable local, state and federal laws, regulations and product characteristics at time of

disposal.

**Empty Container**: Contaminated container should be labeled and disposed in accordance to local, state and federal laws and

regulations.

**General Comments**: Refer to section 6, accidental release measures for additional information.



# 14. Transport Information:

Regulatory Information	UN No.	Proper Shipping Name	UN Class	Packing Group	Labels
US DOT	2686	2-Diethylaminoethanol	8 (3)	II	Corrosive Sticker Flammable Sticker
IMDG	2686	2-Diethylaminoethanol	8 (3)	II	Corrosive Sticker Flammable Sticker
IATA	2686	2-Diethylaminoethanol	8 (3)	II	Corrosive Sticker Flammable Sticker

# 15. Regulatory Information:

**U.S. Federal Regulations:** 

SARA 302 Components: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components: This material does not contain any chemical components with known CAS numbers that exceed the

threshold (De Minimis) reporting levels established by SARA Title III, Section 313

SARA 311/312: Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right to know Components: Diethylethanolamine CAS No. 100-37-8

**Pennsylvania Right to know Components:** Diethylethanolamine CAS No. 100-37-8

New Jersey Right to know Components: Diethylethanolamine CAS No. 100-37-8

California Proposition 65 Components: This product does not contain any chemicals known to the State of California to cause

cancer, birth defects, or any other reproductive harm.

WHMIS Canada: Class B-2: Flammable liquid with a flash point lower than 31°C. Class D-1B: Material causing immediate

and serious toxic effects (TOXIC). Class E: Corrosive liquid

**OSHA Hazcom Standard Rating:** Hazardous

US Toxic Substances Control Act: Listed on the TSCA inventory



### 16. Other Information:

**HMIS and NFPA Rating Scale:** 

**HMIS: Hazardous Materials Identification System** 

Numeric Scale for Health (Blue), Flammability (Red), and Physical Hazard (Yellow):

**HMIS Rating:\*** 

minis Rating.	
HEALTH	3
FLAMMABILITY	2
PHYSICAL HAZARD	0
PERSONAL PROTECTION	С

RATING	HEALTH	FIRE HAZARD	PHYSICAL HAZARD
0	No significant risk to health	Will not burn	Product stable under ambient temperature and condition.
1	Can cause irritation or minor reversible injury.	Must be preheated to burn	Product can become unstable at high temperatures and pressures.
2	Can cause tempo- rary or residual injury	Ignites when moderately heated	Product can become unstable and cause violent chemical reaction at normal pressures and temperatures
3	Can cause serious injury	Ignition occurs at normal temperature	Product capable of forming explosive mixtures and is capable of detonation in presence of
4	Can be lethal from single or repeated exposure.	Extremely flammable	Product is highly explosive and unstable. Exo- thermic reactions possible with decomposition, polymerization, reaction with water or self reaction


Personal Protection Code C: Gloves + Safety Goggles + Chemical Apron

NFPA: National Fire Protection Association

Numeric Scale for Health (Blue), Fire Hazard (Red), and Reactivity (Yellow):

Special (White)

NFPA Rating:\*



RATING	HEALTH	FIRE HAZARD	REACTIVITY
0	Minimal Hazard	Will not burn	Normally Stable
1	Can cause signifi- cant irritation	Must be preheated to burn	Unstable at high temperatures
2	Can cause tempo- rary incapacitation or residual injury	Ignites when moder- ately heated	Normally unstable. Can readily go under violent chemical reaction but do not detonate.
3	Can cause perma- nent injury.	Ignition occurs at nor- mal temperature	Capable of detonation, or of explosive reaction, but requires a strong ignition source.
4	Can be lethal.	Extremely flammable	May explode at normal temperatures and pressures

Revision Date: March 23, 2022

Reason for Revision: Updated logo and contact information. Reviewed for accuracy.

The information contained in this SDS was obtained from current and reliable sources. However, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer/supplier, they are not held responsible for loss, injury, and expense arising out of the product's use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this MSDS.

