

NORTH Metal and Chemical Co.

1. Company Identification and Product Hazard Overview:

Product Name : North Quest 5000; Terpolymer of acrylic acid

Synonyms : N/A

Recommended Use: Used as a scale inhibitor and dispersing agent in industrial water treatment programs

Manufactured for : NORTH Metal and Chemical Company

P. O. Box 1985 609 E. King St. York, PA USA 17405 York, PA USA 17403 Tel: 717-845-8646 Fax: 717-846-7350

Email: north@northmetal.net Website: www.northmetal.net

In Case of Emergency: Call CHEMTREC (24H): 1-800-424-9300

2. Hazard Identification:

GHS Classification:

Acute Toxicity, Oral (Category 5) Acute Toxicity, Inhalation (Category 5) Acute Toxicity, Dermal (Category 5) Eye Damage/Irritation (Category 2B)

Signal Word: WARNING Pictograms: Acute Toxicity



Hazard Statements:

H303 : May be harmful if swallowed H333 : May be harmful is inhaled

H313 : May be harmful in contact with skin

H320 : Causes eye irritation

Precautionary Statements:

P264 : Wash contact area thoroughly after handling

P280 : Wear protective gloves/protective clothing/eye protection/face protection.

P303 + P361 +P353 : IF ON SKIN or hair: Remove/Take off immediately all contaminated clothing. Rinse skin with

water/ shower

P305 + P351 + P338 : IF IN EYES: rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P337 + P313 : If eye irritation persists: Get medical advice/attention

P301 + P330 + P331 : IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P304 + P340 + P310 : IF INHALED: Remove person to fresh air and keep in position comfortable for breathing

P312 : Call a POISON CENTER or doctor/physician if feeling unwell

P403 + P235 : Store in a well-ventilated place. Keep cool.

P273 + P405 : Avoid release to the environment. Store Locked Up.

P501 : Dispose of contents/container in accordance with local/state/federal regulations.

3. Composition/Information on Ingredient:

Chemical Name : North Quest 5000, Terpolymer of acrylic acid

Chemical Family : Acrylic based Terpolymer

Chemical Formula : Not applicable

Substance:	CAS Number:	Hazard	Compo. (%)
Terpolymer of Acrylic Acid	40623-75-4	See Section 2	Proprietary
Water	7732-18-5		Proprietary

4. First Aid Measures:

Eyes: Flush with running water for at least fifteen minutes. If irritation persists, get medical aid.

Skin: Flush with running water for fifteen minutes. If irritation persists, get medical aid.

Ingestion: If the product is swallowed, first rinse mouth with water. Call doctor/physician/poison center

immediately. Do not induce vomiting. Never give anything by mouth to an unconscious person.

If a person vomits, place him/her in recovery position so the vomit does not enter lungs.

Inhalation: If safe to do so, remove individual from further exposure. Keep warm and at rest. If cough or other

symptoms develop, call doctor/poison center immediately.

PPE for first

responders : Gloves and safety goggles are highly recommended.

5. Fire Fighting Measures:

Flash Point (°C) : Above 100 °C/212 °F.

Flammable Limits : Not applicable.

Auto ignition Temp. : Not applicable.

Flammable Class : Not applicable.

Flame Propagation or

Burning Rate of Solids: Not available.

General Hazard : Evacuate personnel downwind in-order to avoid inhalation of irritating and/or harmful fumes and smoke.

Extinguishing Media: Water spray, chemical-type foam. Appropriate for the surrounding area.

Hazardous Combustion

Products : Carbon monoxide, carbon dioxide, sulfur oxides.

Fire Fighting Procedures: This product is a non-flammable substance. However, hazardous decomposition and combustion

products such as carbon and sulfur oxides are formed if product is burning. Cool exposed containers

with water spray to prevent over heating.

Fire Fighting Equipment: Respiratory and eye protection are required for fire fighting personnel. Full protective equipment

(bunker gear) and self-contained breathing apparatus (SCBA) should be used for all indoor fires and any significant outdoor fires. Evacuate area and fight fire from safe distance or a protected location. Move fire-exposed containers, if allowable without sacrificing the safety of the firefighters. If possible,

firefighters should control run-off water to prevent environmental contamination.

Sensitivity to Static Discharge: Not sensitive.

Sensitivity to Mechanical Impact: Not sensitive.



6. Accidental Release Measures:

Protective Gear for Personnel:

For Small Spill: Safety glasses or chemical splash goggles, chemically resistant gloves (rubber/latex), chemically resistant boots, and any appropriate body protection to minimize direct contact to the skin.

For Large Spill: Triple gloves (rubber and nitrile over latex), chemical resistant suit, boots, hard hat, full face mask/an air

purifying respirator (NIOSH approved). Self contained breathing apparatus must be worn in situations where fumigant gas generation and low oxygen levels are a consequence of contamination from the

leak.

Spill Clean-up

Procedures:

For Small Spill: In the event of a small spill, the leak should be contained with an absorbent pad and placed in a properly

labeled waste disposal container immediately. Clean the spill area with water. Do not let chemical/waste

enter the environment

For Large Spill: In the event of a large spill, contain the spill immediately and dispose according to state, federal, and

local hazardous waste regulation. Do not let chemical/waste enter the environment.

Environmental

Precaution: Water spill: use appropriate containment to avoid run off or release to sewer or other waterways.

Land spill: use appropriate containment to avoid run off or release to ground.

General precaution: remove containers of strong acid and alkali from the release area.

Release Notes: If spill could potentially enter any waterway, including intermittent dry creeks, contact local authorities.

7. Handling and Storage:

Handling: Use appropriate personal protective equipment as specified in Section 8. Handle in a well-ventilated

area. Handle in a manner consistent with good industrial/manufacturing techniques and practices. Wash hands thoroughly with soap and water after use. Remove contaminated clothing and protective

equipment before entering eating areas.

Storage : Store in a cool, dry well-ventilated area. Keep containers closed when not in use. Keep product isolated

from incompatible materials/conditions such as freezing temperatures.

8. Exposure Controls and Personal Protection:

Engineering Controls: Use appropriate engineering controls to minimize exposure to vapors generated via routine use. Maintain

adequate ventilation of workplace and storage areas.

Personal Protective

Equipment: Eves and face: Wear safety glasses with side shields or goggles when handling this material.

Skin: Avoid direct contact with skin. Wear rubber gloves, apron, boots or whole bodysuit when

handling this product.

Respiratory: Avoid breathing vapor or mist. Use NIOSH approved respiratory protection equipment when air borne exposure is excessive. If used, full face-piece replaces the need for face shield and/or chemical goggles. Consult the respirator manufacturer to determine the appropriate type of equipment

for a given application.

Work Hygienic Practices: Facilities storing or using this material should be equipped with emergency eyewash, and a safety

shower. Good personal hygiene practices should always be followed.

Exposure Limits:

Substance:	CAS No.:	OSHA STEL	OSHA PEL	ACGIH TLV	ACGIH STEL
Terpolymer of Acrylic Acid	40623-75-4	N/A	N/A	N/A	N/A



9. Chemical and Physical Properties:

Appearance: Clear liquidDecomposition Temp.: Not availableOdor: CharacteristicEvaporation Rate: Not availableOdor threshold: Not availableFlammability: Not flammable

Color : Yellow color Upper Explosive Limit : Not available

PH (1% Solution) : 1.5 - 3.5 **Vapor Pressure** : 3.2 kPa @ 25°C (Water)

Melting Point: > -5°CVapor Density: Not availableFreezing Point: < -5°C</th>Specific Gravity: 1.150 - 1.250

 Boiling Range
 : >100°C
 Solubility
 : Soluble in water

 Flash Point
 : >100°C
 Partition Coefficient
 : Not available

 Viscosity (cPs) @ 25 °C
 : 500 cps max
 Auto Ignition Temp.
 : Not available

10. Stability and Reactivity:

Stability : The product is stable under normal ambient conditions of temperature and pressure.

Polymerization: Polymerization may occur at higher temperatures.

Hazardous

Decomposition Products: Carbon monoxide, carbon dioxide and sulfur oxides.

Incompatible Materials: Strong alkalis, amines, nitrites, sulfites, reducing agents, oxidizing agents.

Conditions to Avoid : Avoid exposure to extreme temperatures, contact with incompatible chemicals, uncontrolled contact

with accelerants.

11. Toxicological Information:

Acute Toxicity:

Oral LD_{50} : > 2500 mg/kg (Rat)**
Dermal LD_{50} : No data available
Inhalation LD_{50} : No data available

Corrosion/Irritation:

Skin : No data available Eyes : No data available.

Sensitization:

Respiratory
Skin
: No data available.

Carcinogenicity
: No data available.

Mutagenicity
: No data available.

Reproductive Effects
: No data available.

Teratogenic Effects
: No data available.
: No data available.

Routes of Exposure: Eyes, Skin, Inhalation.

Long Term Exposure Health Effects:

Eyes : Can cause severe irritation to the eyes if exposure if prolonged.

Skin : Can cause significant irritation if exposure is prolonged.

Inhalation : Can lead to coughing, nasal congestion, tightness of chest and /or shortness of breath.

Ingestion : Can lead to possible nausea or vomiting.



^{**}Classification based on similar product (Polyacrylic acid, CAS No.: 9003-01-4) as no toxicology information is currently available for North *Quest* 5000.

12. Ecological Information:

All work practices must be aimed at eliminating environmental contamination.

Biodegradability : No data available.

Bioaccumulative

Potential : No data available.

Terrestrial Ecotoxicity: This material may be harmful or fatal to contaminated plants or animals,

especially if large volumes are released into the environments.

Aquatic Ecotoxicity: This material may be harmful or fatal to the aquatic environments if large volumes are released.

Aquatic Invertebrates: No data available.

Mobility in Soil: No data available.

Other Adverse Effects: No data available.

13. Disposal Considerations:

Disposal Method: Dispose of waste at an appropriate waste disposal facility according to current applicable laws and

regulations.

For Large Spills : Contain material and call local authorities for emergency assistance.

Product Disposal: Dispose of at a supervised incineration facility or an appropriate waste disposal facility according to

current applicable local, state and federal laws, regulations and product characteristics at time of

disposal.

Empty Container: Contaminated container should be labeled and disposed in accordance to local, state and federal laws and

regulations.

General Comments: Refer to section 6, accidental release measures for additional information.

14. Transport Information:

Regulatory Information	UN No.	Proper Shipping Name	UN Class	Packing Group	Labels
US DOT	None	Not Regulated	None		None
IMDG	None	Not Regulated	None		None
IATA	None	Not Regulated	None		None

15. Regulatory Information:

U.S. Federal Regulations:

TSCA: All components of this product are listed on the TSCA inventory.

CERCLA: Acrylic Acid, RQ - 5000 Lbs (2267.98 KG). RCRA Waste Code: U008 (2-propenoic acid)

SARA TITLE III (EPCRA) Section 302/304: No components of this product were found to be on the hazardous chemicals list.

SARA TITLE III (EPCRA) Section 311/312: Acute health hazard.



16. Other Information:

HMIS and NFPA Rating Scale:

HMIS: Hazardous Materials Identification System

Numeric Scale for Health (Blue), Flammability (Red), and Physical Hazard (Yellow):

HMIS Rating:*

HEALTH	1
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	В


RATING	HEALTH	FIRE HAZARD	PHYSICAL HAZARD
0	No significant risk to health	Will not burn	Product stable under ambient temperature and condition.
1	Can cause irritation or minor reversible injury.	Must be preheated to burn	Product can become unstable at high temperatures and pressures.
2	Can cause temporary or residual injury	Ignites when moderate- ly heated	Product can become unstable and cause violent chemical reaction at normal pressures and temperatures
3	Can cause serious inju- ry	Ignition occurs at nor- mal temperature	Product capable of forming explosive mixtures and is capable of detonation in presence of strong
4	Can be lethal from single or repeated exposure.	Extremely flammable	Product is highly explosive and unstable. Exother- mic reactions possible with decomposition, polymerization, reaction with water or self reac- tion

Personal Protection Code B: Gloves + Safety Goggles

NFPA: National Fire Protection Association

Numeric Scale for Health (Blue), Fire Hazard (Red), and Reactivity (Yellow):

NFPA Rating:*



RATING	HEALTH	FIRE HAZARD	REACTIVITY
0	Minimal Hazard	Will not burn	Normally Stable
1	Can cause signifi- Must be preheated to Unstable at high temperature cant irritation burn		Unstable at high temperatures
2	Can cause tempo- rary incapacitation or residual injury	Ignites when moder- ately heated	Normally unstable. Can readily go under violent chemical reaction but do not detonate.
3	Can cause perma- nent injury.	Ignition occurs at nor- mal temperature	Capable of detonation, or of explosive reaction, but requires a strong ignition source.
4	Can be lethal.	Extremely flammable	May explode at normal temperatures and pressures

Revision Date: May 4, 2022

Reason for Revision: Updated logo and contact information. Formatting. Reviewed for accuracy.

The information contained in this SDS was obtained from current and reliable sources. However, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer/supplier, they are not held responsible for loss, injury, and expense arising out of the product's use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this MSDS.

